

Gas exhaust hose, stainless steel



Skupina produkt	140
Popis média	Speciální
Materiál vnitřní vrstvy hadice	Nerez ocel (1.4016)
Antistatický drát	Ne
Plochá cívka	Ne
Maximální teplota (°C)	700

Spiral wired gas exhaust hose with round cross section and labyrinth profile for e.g. exhaust gases, pellets and granulates. Can also be used as mechanical cable protection.

íslo položky	ID (mm)	OD (mm)	Polomr ohybu (mm)	váha (kg)
14800012	20	24	70	0.5
14800014	22	26	77	0.55
14800016	25	29	86	0.62
14800019	30	34	101	0.73
14800020	32	37	160	0.77
14800022	35	40	170	0.97
14800024	38	43	190	1.05
14800025	40	45	200	1.1
14800026	42	47	210	1.15
14800030	45	50	225	1.23
14800032	50	55	250	1.23
14800038	55	60	265	1.35
14800039	60	65	275	1.46
14800040	65	70	285	1.58
14800044	70	75	300	1.7
14800048	75	80	310	1.81
14800051	80	85	320	1.93
14800053	85	90	335	2.14
14800056	90	95	345	2.17
14800062	100	105	375	2.4



íslo položky	ID (mm)	OD (mm)	Polomr ohybu (mm)	váha (kg)
14800064	102	107	380	2.45
14800068	105	110	390	2.66
14800070	110	115	400	2.64
14800074	115	120	415	2.75
14800076	120	125	425	3.05
14800079	125	130	435	2.99
14800080	127	132	445	3.04
14800082	130	135	450	3.11
14800085	140	145	475	3.56
14800096	150	155	500	3.58
14800160	160	165	525	5.43
14800175	175	175	560	4.17
14800190	190	195	595	6.4
14800200	200	205	620	4.75
14800225	225	230	750	5.34
14800300	300	305	1,000	7.1

