

Straight fitting with male thread pro pneumatics



Skupina produkt	519
Materiál	Hliník
Výrobce	Prevost
Tvar	Rovný
Maximální pracovní tlak (Bar)	16
Rozmr A (mm)	32
Rozmr B (mm)	53
Maximální teplota (°C)	80
Minimální teplota (°C)	-20

íslo položky	OD (mm)	Typ závitu	Závit	Rozmr C (mm)	váha (kg)
54501151606	16	G	G 3/8" Samice	26	0.05
54501151608	16	G	G 1/2" Samice	26	0.05
54501152008	20	G	G 1/2" Samice	32	0.07
54501152012	20	G	G 3/4" Samice	32	0.07
54501152508	25	G	G 1/2" Samice	38	0.13
54501152512	25	G	G 3/4" Samice	38	0.12
54501152516	25	G	G 1" Samice	38	0.12
54501153216	32	G	G 1" Samice	46	0.21
54501153220	32	G	G 1 1/4" Samice	46	0.18
54501154020	40	G	G 1 1/4" Samice	57	0.34
54501154024	40	G	G 1 1/2" Samice	57	0.34
54501155024	50	G	G 1 1/2" Samice	72	0.56
54501155032	50	G	G 2" Samice	72	0.53
54501156332	63	G	G 2" Samice	90	0.98
54501156340	63	G	G 2 1/2" Samice	90	0.93
54501158040	80	G	G 2 1/2" Samice	110	1.53
54501158048	80	G	G 3" Samice	110	1.45

