

COMP CHEM 700



Skupina produkt	140
Barva	Zelená
Popis média	Chemické
Plochá cívka	Ne
Antistatický drát	Ne
Maximální teplota (°C)	-30
Výztužné materiály	Ocelové a pozinkované spirály
Minimální teplota (°C)	80

This hose is suitable as a chemical hose with a wide resistance range. Can be used both as suction and pressure hose. Applications for the hose is loading and unloading of gas trucks and railroad cars, and also within industries in different processes. COMP CHEM 700 is 100% aromatically resistant. Electric continuity is attained when the two spirals are put towards the hose's fittings. In this way, static electricity is avoided. The electrical resistance in an assembled hose is less than 10 Ohm, according to BS 5842:1980 § 6.2. On request, a Special flame resistant version can also be delivered. Supplied in 40m coils. Vacuum = 70%

íslo položky	Pracovní tlak (MPa)	ID (mm)	Metr délky na cívku	Polomr ohybu (mm)	Destrukční tlak (MPa)	Hmotnost (kg/m)	váha (kg)
15822012	2	20	35	75	8	0.6	0.6
15822016	2	25	35	100	8	0.7	0.8
15822020	2	32	35	125	8	0.9	1.1
15822024	1.4	40	35	100	5.6	1.2	1.04
15822032	1.4	50	35	100	5.6	-	2
15822040	1.4	65	35	200	5.6	2.8	1.87
15822048	1.4	75	35	250	5.6	-	3.5
15822064	1.4	100	35	300	5.6	4.5	3.6

